



CT660 6x4 Tractor

Engine	CT13, 475HP @ 1700RPM, 1700-lbft
Radiator	Aluminum, 1564 sq inches
Fan drive	Horton 2-speed direct drive
Exhaust	Horizontal with dual tailpipes
Engine brake	Jake brake, 3 level selector on dash
Alternator	Bosch LH160, 160 amp
Transmission	Eaton RTLO-18918B, 18-Speed
Clutch	Eaton easy-pedal 2050-lbs capacity
Front axle	Meritor MFS-13-143A, 13,200-lbs capcacity
Front Suspension	Multileaf, 14,000-lbs capacity with threaded spring pins
Rear Axle	Meritor MT-40-14X, 40,000-lbs capacity, 3.70 ratio
Traction control	Front and rear locking differential, with indepentant controls in cab
Rear suspension	Hendrickson air HAS402, 40,000-lb capacity, 55" axle spacing, 9.5" height
Tires, Front	Continental 498, 11R22.5, 14-ply
Tires, Rear	Continental 491, 11R22.5, 16-ply
Wheels,	10 polished aluminum 22.5", hub-piloted
Brakes	Spicer extended service S-cam, Front 16.5" x 6", Rear 16.5" x 7"
Brake system	4-channel antilock, automatic slack adjuster, long stroke chambers
Air system	Polished air tanks, Bendix AD9 air drier
Fifth wheel	Fontaine SL7ATB675024, 24" air slide
Frame	Steel, 12.25"x3.38"x.375", 120,000 PSI yield
Wheelbase	201"
Fuel tank	Polished aluminum, 120 gallon with polished straps
Quarter fenders	Polished Stainless steel
Air horns	dual chrome, mounted on cab roof
LED Lighting	Marker lights, tail lights, turn indicator
Fog lights	Mounted in bumper
Cab	Aluminum and fiberglass, air suspended
Interior	Premium level with power windows, power locks, and full gauge pkg
Steering	Tilting and telescoping column, leather steering wheel
Seats	Driver, Highback air suspension / Rider, Highback nonsuspension
Mirrors	Dual axis motorized on both sides, breakaway
Sound system	AM/FM/CD/Ipod input with (4) premium coaxial speakers
CB Instal Pkg	Antenna, power leads, mounting base
Cab storage	on back wall and door panels
Paint	Red, single color Basecoat/clearcoat